

# A.G.I. envirotank

## Double Wall Heated Water

AGI has designed a heated double wall Envirotank for produced water.

A catadyne heater is used to heat the air space between the inner and outer tanks. This heat keeps the tank's contents moveable even in the severest of Canadian winters.



### The Envirotank Advantage

- ◆ No dikes, liners, gravel or excavation
- ◆ Requires 50% less installation area as opposed to a single wall tank with a dike
- ◆ Quick & easy to install and relocate
- ◆ One tank relocation pays for the extra cost of the double wall tank
- ◆ **Meets Guideline 55** and or API standards
- ◆ Our Envirotanks are shipped with the heater already installed. (Not in a box for field install.)
- ◆ AGI's unique corner cabinet allows our tanks to be moved without pilot cars on standard highboy trailers.

### Standard Features

- ◆ **Guide Line 55** labeled or **API** certified
- ◆ **110% containment** (no dike required)
- ◆ Lifting and tailing lugs
- ◆ Normal venting for both primary and secondary tanks
- ◆ 3" fill c/w check valve
- ◆ 3" discharge c/w valve, camlock & stinger
- ◆ 3/4" sight glass for containment space
- ◆ 8" thief hatch (sweet service)
- ◆ Open style gauge board in cubic meters
- ◆ Catadyne Infra-red gas heater
- ◆ 12 volt heater leads
- ◆ Thermostatic temperature control valve
- ◆ Pressure gauge and regulator
- ◆ Vent hood assembly
- ◆ 1 1/2" urethane foam c/w black elastomeric seal
- ◆ Elevated tank floor (For free heat movement in containment)
- ◆ Cabinet for heater and valves



**Optional Features**

- ◆ Bottom skid (Recommended on tanks 100 Barrels and smaller)
- ◆ L-skid (Recommended on tanks 200 Barrels and larger)
- ◆ Heater fired with Natural Gas or Propane
- ◆ Sealed gauge board or electronic level gauge
- ◆ Thief hatch for sour service
- ◆ Epoxy lining of tank interior
- ◆ Upgrade urethane foam to 2"
- ◆ Upgrade urethane foam to aluminum clad insulation
- ◆ High and or low level switches. (electric or pneumatic)
- ◆ Ladder with cage
- ◆ Custom colors
- ◆ Custom capacity and dimensions

Dimensional Chart					
Capacity	Inner Tank Dia. I.D.	Inner Tank Height	Outer Tank Dia. O.D.	Outer Tank Height	Weight
50 BBL (7,950 L)	93"	72"	99"	72"	4,500 lbs
100 BBL (15,910 L) <b>Stock Item</b>	132"	72"	141"	72"	5,500 lbs
210 BBL (33,413 L) <b>Stock Item</b>	118"	192"	127"	192"	8,700 lbs
300 BBL ( L)	144"	177.5"	150"	180"	13,500 lbs
400 BBL (63,364 L) <b>Stock Item</b>	144"	240"	153"	240"	18,000 lbs

**AGI Biggar, Saskatchewan, Canada 1-800-746-6646 www.Envirotank.com**