

A.G.I. envirotank









Single Heated







AGI can design and build an oilfield tank to meet your needs.

At AGI we have our own in house tank lining and insulating facility. Our quality is very high and documented.





Standard Features

-  API labeled
-  Lift lugs & tailing lugs
-  Ladder and cage
-  Loading pads
-  Open style gauge board (Cubic Meter)
-  5 - four inch flanges
-  Sandblasted to SSPC-SP6 (brush blast)
-  Urethane insulation with black elastomeric seal

Optional Features

-  Ladder with cage
-  Tank lining Devoe, Enviroline Philips etc..
-  Heavy duty L-skid
-  Sour service thief Hatch & gaskets

More Optional Features

-  Sealed sour service gauge board
-  Urethane or aluminum clad insulation
-  Fire tubes, immersion heaters or steam coils
-  Butterfly valves & plugs

| Capacity | Diameter | | Height | | Weight | |
|----------|----------|---------|--------|---------|------------|----------|
| | | | | | | |
| 400 bbl | 12' | 3657 mm | 20' | 6096 mm | 11,000 lbs | 4,990 kg |
| 500 bbl | 12' | 3657 mm | 25' | 7620 mm | 12,500 lbs | 5,670 kg |
| 750 bbl | 15'3" | 4648 mm | 24' | 7315 mm | 14,000 lbs | 6,350 kg |
| 1000 bbl | 15'3" | 4648 mm | 32' | 9754 mm | 17,000 lbs | 7,711 kg |
| 1000 bbl | 21' 6" | 6553 mm | 16' | 4877 mm | 18,000 lbs | 8,165 kg |
| 1500 bbl | 21' 6" | 6553 mm | 24' | 7315 mm | 22,000 lbs | 9,979 kg |
| 2000 bbl | 23' 6" | 7163 mm | 26' | 7925 mm | 27,000 lbs | 12,247kg |

AGI Biggar, Saskatchewan, Canada 1-800-746-6646 www.Envirotank.com