

A.G.I. envirotank









Single Heated







AGI can design and build an oilfield tank to meet your needs.

At AGI we have our own in house tank lining and insulating facility. Our quality is very high and documented.





Standard Features

-  API labeled
-  Lift lugs & tailing lugs
-  Ladder and cage
-  Loading pads
-  Open style gauge board (Cubic Meter)
-  5 - four inch flanges
-  Sandblasted to SSPC-SP6 (brush blast)
-  Urethane insulation with black elastomeric seal

Optional Features

-  Ladder with cage
-  Tank lining Devoe, Enviroline Philips etc..
-  Heavy duty L-skid
-  Sour service thief Hatch & gaskets

More Optional Features

-  Sealed sour service gauge board
-  Urethane or aluminum clad insulation
-  Fire tubes, immersion heaters or steam coils
-  Butterfly valves & plugs

Capacity	Diameter		Height		Weight	
400 bbl	12'	3657 mm	20'	6096 mm	11,000 lbs	4,990 kg
500 bbl	12'	3657 mm	25'	7620 mm	12,500 lbs	5,670 kg
750 bbl	15'3"	4648 mm	24'	7315 mm	14,000 lbs	6,350 kg
1000 bbl	15'3"	4648 mm	32'	9754 mm	17,000 lbs	7,711 kg
1000 bbl	21' 6"	6553 mm	16'	4877 mm	18,000 lbs	8,165 kg
1500 bbl	21' 6"	6553 mm	24'	7315 mm	22,000 lbs	9,979 kg
2000 bbl	23' 6"	7163 mm	26'	7925 mm	27,000 lbs	12,247kg

AGI Biggar, Saskatchewan, Canada 1-800-746-6646 www.Envirotank.com